


Product Technical Parameters

| Place of Origin | Zhongshan, Guangdong, China | Product Image |
|-------------------------|---|--|
| Brand Name | Jin Yuan |  |
| Model Number | JY-B001-300W | |
| Product name | split type solar streets light | |
| Power/Watts | 300W | |
| Lamp Body Material | Die-Casting Aluminum | |
| Product Size | 660*265*100mm | |
| Solar panel | 18V 120W (A grade polycrystalline silicon) | |
| solar panel size | 1200*670*30mm | |
| Power Supply Capacity | 12.8V 30AH | |
| Battery Type | LIFEPO4 lithium battery | |
| LED Light Source | 5054 lamp beads, 200/PCS | |
| Color Temperature(CCT) | 3500K-7500K | |
| IP Rating | IP65 | |
| Lumens: (lm/w) | 130LM/W | |
| Lifespan (hours) | 50000 hours | |
| Charging time(hours) | 5-8 hours (the weather is fine) | |
| Working Time (hours) | 12-15 hours, 2-3 rainy days | |
| Warranty(Year) | 2 years | |
| Work Mode Function | Optical Control + Remote Control | |
| Product shell lifespan | 10-Year | |
| Support Dimmer | Yes | |
| Beam Angle(°) | 90° | |
| CRI (Ra>) | 80 | |
| Input Voltage(V) | DC 6V | |
| Working Temperature(°C) | 20-60°C | |
| Application | High Ways、Garden、Private Houses、Street、Park、Courtyard、Roadwa、Country roads, | |
| Certification | RoHS, CE | |


Product Technical Parameters

| Place of Origin | Zhongshan, Guangdong, China | Product Image |
|--------------------------|---|---|
| Brand Name | Jin Yuan |  |
| Model Number | JY-B001-200W | |
| Product name | split type solar streets light | |
| Power/Watts | 200W | |
| Lamp Body Material | Die-Casting Aluminum | |
| Product Size | 660*265*100mm | |
| Solar panel | 18V 120W (A grade polycrystalline silicon) | |
| solar panel size | 1200*670*30mm | |
| Power Supply Capacity | 3.2V 120AH | |
| Battery Type | LIFEP04 lithium battery | |
| LED Light Source | 5054 lamp beads, 200/PCS | |
| Color Temperature (CCT) | 3500K-7500K | |
| IP Rating | IP65 | |
| Lumens: (lm/w) | 130LM/W | |
| Lifespan (hours) | 50000 hours | |
| Charging time (hours) | 5-8 hours (the weather is fine) | |
| Working Time (hours) | 12-15 hours, 2-3 rainy days | |
| Warranty (Year) | 2 years | |
| Work Mode Function | Optical Control + Remote Control | |
| Product shell lifespan | 10-Year | |
| Support Dimmer | Yes | |
| Beam Angle(°) | 90° | |
| CRI (Ra>>) | 80 | |
| Input Voltage (V) | DC 6V | |
| Working Temperature (°C) | 20-60°C | |
| Application | High Ways、Garden、Private Houses、Street、Park、Courtyard、Roadwa、Country roads, | |
| Certification | RoHS, CE | |

Product Technical Parameters

| Place of Origin | Zhongshan, Guangdong, China | Product Image |
|--------------------------|--|---|
| Brand Name | Jin Yuan |  |
| Model Number | JY-B001-150W | |
| Product name | split type solar streets light | |
| Power/Watts | 150W | |
| Lamp Body Material | Die-Casting Aluminum | |
| Product Size | 600*245*900mm | |
| Solar panel | 6V 15W Polycrystalline Silicon | |
| solar panel size | 1020*670*30mm | |
| Power Supply Capacity | 3.2V 100AH | |
| Battery Type | LIFEP04 lithium battery | |
| LED Light Source | 5054 lamp beads, 150/PCS | |
| Color Temperature (CCT) | 3500K-7500K | |
| IP Rating | IP65 | |
| Lumens: (lm/w) | 130LM/W | |
| Lifespan (hours) | 50000 hours | |
| Charging time (hours) | 5-8 hours (the weather is fine) | |
| Working Time (hours) | 12-15 hours, 2-3 rainy days | |
| Warranty (Year) | 2 years | |
| Work Mode Function | Optical Control + Remote Control | |
| Product shell lifespan | 10-Year | |
| Support Dimmer | Yes | |
| Beam Angle(°) | 90° | |
| CRI (Ra>>) | 80 | |
| Input Voltage (V) | DC 6V | |
| Working Temperature (°C) | 20-60°C | |
| Application | High Ways, Garden, Private Houses, Street, Park, Courtyard, Roadwa, Country roads, | |
| Certification | RoHS, CE | |

Product Technical Parameters

| Place of Origin | Zhongshan, Guangdong, China | Product Image |
|-------------------------|--|--|
| Brand Name | Jin Yuan |  |
| Model Number | JY-B001-100W | |
| Product name | split type solar streets light | |
| Power/Watts | 100W | |
| Lamp Body Material | Die-Casting Aluminum | |
| Product Size | 550*225*90mm | |
| Solar panel | 18V 80W (A grade polycrystalline silicon) | |
| solar panel size | 820*670*30mm | |
| Power Supply Capacity | 3.2V 80AH | |
| Battery Type | LIFEPO4 lithium battery | |
| LED Light Source | 5054 lamp beads, 100/PCS | |
| Color Temperature (CCT) | 3500K-7500K | |
| IP Rating | IP65 | |
| Lumens: (lm/w) | 130LM/W | |
| Lifespan (hours) | 50000 hours | |
| Charging time(hours) | 5-8 hours (the weather is fine) | |
| Working Time (hours) | 12-15 hours, 2-3 rainy days | |
| Warranty(Year) | 2 years | |
| Work Mode Function | Optical Control + Remote Control | |
| Product shell lifespan | 10-Year | |
| Support Dimmer | Yes | |
| Beam Angle(°) | 90° | |
| CRI (Ra>) | 80 | |
| Input Voltage(V) | DC 6V | |
| Working Temperature(°C) | 20-60°C | |
| Application | High Ways, Garden, Private Houses, Street, Park, Courtyard, Roadwa, Country roads, | |
| Certification | RoHS, CE | |

Product Technical Parameters

| | | |
|-------------------------|---|--|
| Place of Origin | Zhongshan, Guangdong, China | |
| Brand Name | Jin Yuan | |
| Model Number | JY-B001-50W | |
| Product name | split type solar streets light | |
| Power/Watts | 50W | |
| Lamp Body Material | Die-Casting Aluminum | |
| Product Size | 500*210*85mm | |
| Solar panel | 6V 50W (A grade polycrystalline silico | |
| solar panel size | 670*535*25mm | |
| Power Supply Capacity | 3.2V 40AH | |
| Battery Type | LIFEPO4 lithium battery | |
| LED Light Source | 5054 lamp beads, 60/PCS | |
| Color Temperature (CCT) | 3500K-7500K | |
| IP Rating | IP65 | |
| Lumens: (lm/w) | 130LM/W | |
| Lifespan (hours) | 50000 hours | |
| Charging time (hours) | 5-8 hours (the weather is fine) | |
| Working Time (hours) | 12-15 hours, 2-3 rainy days | |
| Warranty (Year) | 2 years | |
| Work Mode Function | Optical Control + Remote Control | |
| Product shell lifespan | 10-Year | |
| Support Dimmer | Yes | |
| Beam Angle(°) | 90° | |
| CRI (Ra>) | 80 | |
| Input Voltage(V) | DC 6V | |
| Working Temperature(°C) | 20-60°C | |
| Application | High Ways、 Garden、 Private Houses、 Street、 Park、 Courtyard、 Roadwa、 | |
| Certification | RoHS, CE | |