Product Technical Parameters				
Place of Origin	Zhongshan, Guangdong, China	Product Image		
Brand Name	Jin Yuan			
Model Number	JY-B003-800W			
Product name	split type solar streets light			
Power/Watts	800W			
Lamp Body Material	Die-Casting Aluminum			
Product Size	640*257*80mm			
Solar panel	6V 80W (A grade plolycrystalline silicon)			
solar panel size	820*670*30mm			
Power Supply Capacity	3. 2V 80AH			
Battery Type	LIFEPO4 lithium battery			
LED Light Source	3030 lamp beads, 180/PCS			
Color Temperature (CCT)	3500K-7500K			
IP Rating	IP65			
Lumens: (1m/w)	130LM/W			
Lifespan (hours)	30000 hours			
Charging time(hours)	5-8 hours (the weather is fine)			
Working Time (hours)	12-15 hours, 2-3 rainy days	The		
Warranty (Year)	2 years			
Work Mode Function	Optical Control + Remote Control+ radar induction			
Product shell lifespan	10-Year			
Support Dimmer	Yes			
Beam Angle(°)	90°			
CRI (Ra>)	80			
Input Voltage(V)	DC 6V			
Working Temperature(℃)	20−60℃			
Application	High Ways, Garden, Private Houses, Street, Park, Courtyard, Roadwa, Country roads,			
Certification	Rohs, CE			

Product Technical Parameters				
Place of Origin	Zhongshan, Guangdong, China	Product Image		
Brand Name	Jin Yuan			
Model Number	JY-B003-600W	_		
Product name	split type solar streets light	_		
Power/Watts	600W			
Lamp Body Material	Die-Casting Aluminum			
Product Size	640*257*80mm			
Solar panel	6V 60W (A grade plolycrystalline silicon)	_		
solar panel size	640*670*25mm	_		
Power Supply Capacity	3. 2V 60AH			
Battery Type	LIFEPO4 lithium battery			
LED Light Source	3030 lamp beads, 180/PCS			
Color Temperature(CCT)	3500K-7500K			
IP Rating	IP65	G ,		
Lumens: (1m/w)	130LM/W			
Lifespan (hours)	50000 hours			
Charging time (hours)	5-8 hours (the weather is fine)			
Working Time (hours)	12-15 hours, 2-3 rainy days			
Warranty (Year)	2 years			
Work Mode Function	Optical Control + Remote Control+ radar induction			
Product shell lifespan	10-Year	-		
Support Dimmer	Yes			
Beam Angle(°)	90°	1		
CRI (Ra>)	80	1		
Input Voltage(V)	DC 6V	1		
Working Temperature(°C)	20−60℃	1		
Application	High Ways, Garden, Private Houses, Street, Park, Courtyard, Roadwa, Country roads,	1		
Certification	RoHS, CE			

Product Technical Parameters				
Place of Origin	Zhongshan, Guangdong, China	Product Image		
Brand Name	Jin Yuan			
Model Number	JY-B003-500W			
Product name	split type solar streets light			
Power/Watts	500W			
Lamp Body Material	Die-Casting Aluminum			
Product Size	640*257*80mm			
Solar panel	6V 35W (A grade plolycrystalline silicon)			
solar panel size	700*350*16mm			
Power Supply Capacity	3. 2V 35AH			
Battery Type	LIFEPO4 lithium battery			
LED Light Source	3030 lamp beads, 180/PCS			
Color Temperature (CCT)	3500K-7500K			
IP Rating	IP65			
Lumens: (1m/w)	130LM/W			
Lifespan (hours)	30000 hours			
Charging time(hours)	5-8 hours (the weather is fine)			
Working Time (hours)	12-15 hours, 2-3 rainy days			
Warranty (Year)	2 years			
Work Mode Function	Optical Control + Remote Control+ radar induction			
Product shell lifespan	10-Year			
Support Dimmer	Yes			
Beam Angle(°)	90°			
CRI (Ra>)	80			
Input Voltage(V)	DC 6V			
Working Temperature(℃)	20-60℃			
Application	High Ways, Garden, Private Houses, Street, Park, Courtyard, Roadwa, Country roads,			
Certification	RoHS, CE			

Product Technical Parameters				
Place of Origin	Zhongshan, Guangdong, China	Product Image		
Brand Name	Jin Yuan			
Model Number	JY-B003-400W			
Product name	split type solar streets light			
Power/Watts	400W			
Lamp Body Material	Die-Casting Aluminum			
Product Size	512*206*45mm			
Solar panel	6V 30W (A grade plolycrystalline silicon)			
solar panel size	600*350*16mm			
Power Supply Capacity	3. 2V 30AH			
Battery Type	LIFEPO4 lithium battery			
LED Light Source	5054 lamp beads, 50/PCS			
Color Temperature (CCT)	3500K-7500K			
IP Rating	IP65			
Lumens: (1m/w)	130LM/W			
Lifespan (hours)	50000 hours			
Charging time(hours)	5-8 hours (the weather is fine)			
Working Time (hours)	12-15 hours, 2-3 rainy days			
Warranty(Year)	2 years			
Work Mode Function	Optical Control + Remote Control+ radar induction			
Product shell lifespan	10-Year			
Support Dimmer	Yes			
Beam Angle(°)	90°			
CRI (Ra>)	80			
Input Voltage(V)	DC 6V			
Working Temperature(℃)	20−60℃			
Application	High Ways、Garden、Private Houses、Street、 Park、Courtyard、Roadwa、Country roads,			
Certification	RoHS, CE			